

# **Safety Data Sheet**

Issuing Date 21-Mar-2012 Revision Date 26-June-2015 Version 2

#### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product number 7012

Product identifier Extreme Penetrating Oil (Aerosol)

Company information The Lubri-Loy Comany 150 Enterprise Dr.

Wentzville, MO 63385

Company phone General Assistance (636) 561-5007

Emergency telephone US Chemtrec: 1-800-424-9300

Recommended use Lubricant
Recommended restrictions None known.

# 2. HAZARDS IDENTIFICATION

Physical hazardsFlammable aerosolsCategory 1Health hazardsAspiration hazardCategory 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response If swallowed: Immediately call a poison center/doctor. If exposed or concerned: Get medical

advice/attention. Do NOT induce vomiting.

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS **Mixtures** Chemical name % Common name and synonyms **CAS** number Distillates (Petroleum), 64742-47-8 40 - 60 **Hydrotreated Light** Distillates, Petroleum, 64742-65-0 10 - 20Solvent-dewaxed Heavy Paraffinic Diethylene Glycol Monobutyl Ether 112-34-5 2.5 - 10

Chemical name	Common name and synonyms	CAS number	%
Propane		74-98-6	2.5 - 10
Other components below reports		10 - 20	

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

1 E	IRST	A ID	CII	DEC
4 F	IKS I	$\Delta H$		RES.

If symptoms develop move victim to fresh air. Get medical attention if symptoms persist. Inhalation

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

General information

Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Unsuitable extinguishing media

Specific hazards arising from

the chemical Special protective equipment

and precautions for firefighters

Fire-fighting equipment/instructions

Specific methods

General fire hazards

Alcohol resistant foam. Water fog. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol.

# **6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas, Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Never return spills in original containers for re-use.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

#### 7. HANDLING AND STORAGE

#### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition, All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Value

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

	Occu	pational	exposure	limits
--	------	----------	----------	--------

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm	
US. ACGIH Threshold Limit Valu Components	es Type	Value	Form
Diethylene Glycol Monobutyl Ether (CAS	TWA	10 ppm	Inhalable fraction and vapor.

No biological exposure limits noted for the ingredient(s).

Monobutyl Ether (CAS 112-34-5)

US. NIOSH: Pocket Guide to Chemical Hazards Components Type

TWA Propane (CAS 74-98-6) 1800 mg/m3 1000 ppm

**Biological limit values** 

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

Face shield is recommended. Wear safety glasses with side shields (or goggles). Eye/face protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear suitable protective clothing.

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an Respiratory protection

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** 

Physical state Gas. **Form** Aerosol.

Amber, Dark brown. Color characteristic Odor Not available. Odor threshold

Not available. pΗ Melting point/freezing point Not available.

Initial boiling point and boiling

182.69 °F (83.71 °C) estimated

range

Flash point -156.0 °F (-104.4 °C) Propellant estimated

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

0.9 % estimated

Flammability limit - upper

9.5 % estimated

(%)

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%)

Vapor pressure 38 - 48 psig @70F estimated

Not available. Vapor density Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

490.98 °F (254.99 °C) estimated Auto-ignition temperature

Not available. **Decomposition temperature** Not available. Viscosity

Other information

33 in estimated Flame extension

Specific gravity 0.831 - 0.851 estimated

# 10. STABILITY AND REACTIVITY

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

occur.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the Conditions to avoid

flash point. Contact with incompatible materials.

Incompatible materials Hazardous decomposition

products

Strong oxidizing agents. Fluorine. Chlorine. Nitrates. No hazardous decomposition products are known.

# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious Ingestion

chemical pneumonia. Smallest quantities reaching the lungs through swallowing or subsequent

No dangerous reaction known under conditions of normal use. Hazardous polymerization does not

vomiting may result in lung edema or pneumonia.

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. Aspiration may cause pulmonary edema and pneumonitis. Direct contact with

eyes may cause temporary irritation.

# Information on toxicological effects

May be fatal if swallowed and enters airways. Expected to be a low hazard for usual industrial or Acute toxicity

commercial handling by trained personnel.

Components **Species Test Results** 

Diethylene Glycol Monobutyl Ether (CAS 112-34-5)

Acute

Dermal

LD50 Guinea pig 2 ml/kg, 2 Days

> Rabbit 2764 mg/kg, 24 Hours

Oral

LD100 Rabbit 4000 mg/kg LD50 Guinea pig 2000 mg/kg Mouse 2410 mg/kg

> 2500 - 3000 mg/kg Rabbit

Rat 3306 mg/kg

Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

> 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat > 7.5 mg/l, 6 Hours

> 4.6 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Distillates, Petroleum, Solvent-dewaxed Heavy Paraffinic (CAS 64742-65-0)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

> 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat > 2.5 mg/l, 4 Hours

Oral

LD50 Rat 5000 mg/kg

Propane (CAS 74-98-6)

Acute

Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat 1355 mg/l

658 mg/I/4h

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

# 12. ECOLOGICAL INFORMATION

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product Species Test Results

L1 LUBRICANT PROTECTANT (CAS Mixture)

Aquatic

Crustacea EC50 Daphnia 5668.3096 mg/L, 48 Hours estimated

Fish LC50 Fish 17.2181 mg/L, 96 Hours estimated

Components Species Test Results

Diethylene Glycol Monobutyl Ether (CAS 112-34-5)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) 1300 mg/l, 96 hours

Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 2.9 mg/l, 96 hours

(Oncorhynchus mykiss)

\* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Diethylene Glycol Monobutyl Ether 0.56
Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. DISPOSAL CONSIDERATIONS

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

# 14. TRANSPORT INFORMATION

DOT

UN number UN1950

**UN proper shipping name** Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1 Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisions N82 Packaging exceptions 306 Packaging non bulk None Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### IATA

UN1950 **UN** number

UN proper shipping name

Aerosols, flammable

Allowed.

LTD QTY

Not applicable.

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

**Environmental hazards** No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Cargo aircraft only Allowed. **Packaging Exceptions** LTD QTY

**IMDG** 

**UN** number UN1950 **AEROSOLS UN** proper shipping name

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Not applicable. Packing group

**Environmental hazards** 

Marine pollutant No. **EmS** F-D. S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT





# 15. REGULATORY INFORMATION

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

(SDWA)

**US state regulations** 

**US. Massachusetts RTK - Substance List** 

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Propane (CAS 74-98-6)

US. Rhode Island RTK

Propane (CAS 74-98-6)

**US. California Proposition 65** 

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

#### **16. OTHER INFORMATION**

Revision date 06-26-2015

Version # 02

(M)SDS sections updated 2 3 5 7 9 10 11 14 16

#### **Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

Revision Information Product and Company Identification: Alternate Trade Names

Transport Information: Material Transportation Information

GHS: Classification

**End of SDS** 

Product name: L1 LUBRICANT PROTECTANT

SDS US

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).