

# **Safety Data Sheet**

Issuing Date 19-May-2014 Revision Date 19-May-2014 Version 1

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product name Automotive Synthetic Gear Oil LS GL-5 75W-90

Other means of identification

Product Code(s)

Synonyms

AGOS-7W9, AGOS-7W9-640
No information available

Recommended use of the chemical and restrictions on use
Recommended Use Gear Oil, Lubricant.
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address The Lubri-Loy Company 150 Enterprise Dr. Wentzville, MO 63385 TEL: (636) 561-5007

Emergency telephone number
Company Emergency Phone
Number
(636) 561-5007
(636) 561-5007

Emergency telephone number Chemtrec 1-800-424-9300

# 2. HAZARDS IDENTIFICATION

# Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Gases)	Category 4
Skin sensitization	Category 1

#### Label elements

#### **EMERGENCY OVERVIEW**

# WARNING

#### Hazard statements

Harmful if inhaled

May cause an allergic skin reaction



Appearance Amber colored liquid Physical state viscous liquid Odor Mild petroleum odor Mild sulfur odor

Revision Date 19-May-2014

#### **Precautionary Statements - Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves

### **Precautionary Statements - Response**

Specific treatment (see supplemental first aid instruction on this label)

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

#### Other information

- May be harmful in contact with skin
- · Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

Unknown Aquatic Toxicty 0% of the mixture consists of ingredient(s) of unknown toxicity

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Common NameSynthetic hydrocarbon lubricating fluid.Chemical FamilyPetroleum hydrocarbon mixture.

Chemical name	CAS-No	Weight %	Trade secret
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	56.83	*
Residual Oils (petroleum), solvent-dewaxed	64742-62-7	0-40	*
Poly long-chain alkyl methacrylate	Proprietary	1.26-2.1	*
Long-chain alkyl amine	Proprietary	0.26-0.52	*
Long-chain alkenyl amine	Proprietary	0.05-0.26	*
Alkyl Phosphonate	Proprietary	0.05-0.26	*
Alkoxylated long-chain alkanol borate	Proprietary	0.12-0.24	*
Long-chain alkyl amine	Proprietary	0.04-0.18	*
Long-chain alkyl amine	Proprietary	0.02-0.12	*
Alkyl dithio thiadiazole	Proprietary	0.02-0.12	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

#### First aid measures

**General advice** No hazards which require special first aid measures.

**Eye contact** Flush eyes for 30 minutes with water. Get medical attention if irritation persists.

**Skin contact** Wash off immediately with soap and plenty of water.

**Inhalation** Move exposed persons to fresh air. Consult medical personnel if breathing issues occur.

**Ingestion** Do NOT induce vomiting. Consult a physician.

Most important symptoms and effects, both acute and delayed

Revision Date 19-May-2014

**Symptoms** No information available.

Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>). Dry chemical. Foam. Water can be used to keep surrounding materials cool.

**Small Fires** Always use personal safety equipment. Follow appropriate personal safety procedures, and

extinguishing media.

Contact emergency personnel. Large Fires

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

## Specific hazards arising from the chemical

Combustible material.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

**Explosion data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal protection Avoid contact with the skin and the eyes. Eye protection or face shield should be used if

material is used under conditions that increase the chances of splattering. Wash skin with soap and water if contact occurs. Launder soiled clothing. If spilled, take caution, as

material can cause surfaces to become very slippery.

Clean up area with absorbent material and place in closed containers for disposal. Ventilate For emergency responders

the area.

**Environmental precautions** 

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Cover with earth, sand, or other non-combustible material followed with plastic sheets to **Methods for containment** 

minimize spreading or contact with rain.

Excess liquid material can be collected using a scoop or shovel and stored for recycling or Methods for cleaning up

disposal. Prevent material from entering drains or waterways.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes and clothing. Eye protection or face shield should be used if

material is used under conditions that increase the chances of splattering. If contact is made, wash skin with soap and water. Launder soiled clothing. Maximum handling temperature is 70 degrees C (158 F). It is recommended to pump or transfer material at

ambient temperature.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat and sources of ignition. Keep containers closed when not in use.

Follow first aid measures if contact occurs, and spill procedures if spill occurs. For packaged material: Store in a cool dry area. For bulk material: store in cool dry area. Always follow local, state, and federal guidlines for storage of material for amount stored.

Incompatible Products Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines This product does not contain any hazardous materials with occupational exposure limits

established by the region specific regulatory bodies.

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/face Protection** If splashes are likely to occur, wear:. Goggles. Eye/face Protection.

**Skin and body protection**Long sleeved clothing. Protective gloves can be worn, if material comes in contact with skin

wash with soap and water.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

**General Hygiene Considerations** Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state viscous liquid

Appearance Amber colored liquid Odor Mild petroleum odor Mild

sulfur odor

Color amber Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available
Melting point/freezing point
Boiling Point/Range No information available
Flash point > 93.3 °C / > 200 °F
Evaporation rate No information available
Flammability (solid, gas)
Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Specific gravity 0.87

Water solubility
Solubility in other solvents
Partition coefficient
No information available
No information available
No information available

**Autoignition temperature** 

Decomposition temperatureNo information availableKinematic viscosity110-120 @40C mm2/sDynamic viscosityNo information availableExplosive propertiesNo information availableOxidizing propertiesNo information available

**Other information** 

Softening point
VOC Content
Density
No information available

## 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

### **Chemical stability**

Stable under normal conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous polymerization** Hazardous polymerization does not occur.

## **Conditions to avoid**

Excessive heat. High energy sources of ignition.

## **Incompatible materials**

Strong oxidizing agents.

#### **Hazardous decomposition products**

None known based on information supplied.

#### 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

Product Information No data available

Inhalation Inhalation of vapors in high concentration may cause irritation of respiratory system.

**Eye contact** Avoid contact with eyes. May cause irritation.

**Skin contact** May cause eye/skin irritation. Repeated exposure may cause skin dryness or cracking.

**Ingestion** Do NOT taste or swallow.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Residual Oils (petroleum), solvent-dewaxed 64742-62-7	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	= 2.18 mg/L (Rat)4 h

Long-chain alkyl amine	612 mg/kg ( Rat )	251 mg/kg ( Rat )	157 ppm ( Rat ) 4h
Long-chain alkenyl amine	1689 mg/kg ( Rat )	-	-
Alkyl Phosphonate	3200 mg/kg ( Rat )	1990 mg/kg ( Rabbit )	-
Long-chain alkyl amine	612 mg/kg ( Rat )	251 mg/kg ( Rat )	-
Long-chain alkyl amine	612 mg/kg ( Rat )	251 mg/kg ( Rat )	157 ppm ( Rat )

### Information on toxicological effects

**Symptoms** No information available.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

Germ cell mutagenicity

Carcinogenicity

May cause sensitization by skin contact.

No information available.

Mineral oils are known to cause cancer because of carcinogenic components (e.g. benzene). The mineral oil in this product is highly refined and should not be considered a carcinogen. Used lubricating oil may contain hazardous components which have the potential to cause skin cancer. Continuous long-term contact with used lubricating oils has caused skin cancer in animal tests.

Chemical name **ACGIH** IARC **NTP** OSHA Petroleum distillates, Group 1 Х hydrotreated heavy paraffinic 64742-54-7 Residual Oils (petroleum), Group 1 Χ solvent-dewaxed 64742-62-7

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration hazard
No information available.
No information available.
No information available.

## Numerical measures of toxicity - Product Information

Unknown Aquatic Toxicty 0% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 5287 mg/kg ATEmix (dermal) 2983 mg/kg ATEmix (inhalation-gas) 17018 ppm

#### 12. ECOLOGICAL INFORMATION

## **Ecotoxicity**

Harmful to aquatic life

Harmful to aquatic life with long lasting effects

3.28% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	-	5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
Residual Oils (petroleum), solvent-dewaxed 64742-62-7	-	5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50

## Synthetic LS GL-5 75W-90 Gear Oil

## Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Other adverse effects No information available

## 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Method Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

# 14. TRANSPORT INFORMATION

**DOT** Not regulated

IATA PETROLEUM LUBRICATING OIL; NOT REGULATED AS DANGEROUS GOODS FOR

TRANSPORT UNDER ICAO TI OR IATA DGR

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Does not comply **DSL/NDSL** Does not comply **EINECS/ELINCS** Does not comply **ENCS** Does not comply Does not comply **IECSC** Does not comply **KECL PICCS** Does not comply **AICS** Does not comply

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## **U.S. Federal Regulations**

## **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

## SARA 311/312 Hazard Categories

Acute health hazardNoChronic Health HazardNoFire hazardNoSudden release of pressure hazardNoReactive HazardNo

#### **Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

# **U.S. State Regulations**

## **California Proposition 65**

This product contains the following Proposition 65 chemicals: 2-Propenoic Acid, Ethyl Ester

#### **U.S. State Right-to-Know Regulations**

## U.S. EPA Label Information

EPA Pesticide registration number Not Applicable

#### **16. OTHER INFORMATION**

NFPA Health hazards 1 Flammability 1 Instability 0 Physical and Chemical

Hazards -

HMIS Health hazards 1 Flammability 1 Physical hazards 0 Personal protection X

Issuing Date19-May-2014Revision Date19-May-2014

**Revision Note** 

(M)SDS sections updated 2 3 5 9 11 12 14 16

# **Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of MSDS**