

# **Safety Data Sheet**

Issuing Date 02-Feb-2010 Revision Date 26-June-2014 Version 2

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name Synthetic GL-2 EP Industrial Gear Oils: ISO 68, 100, 150, 220, 320, 460, 680

Other means of identification GOS-068, GOS-068-640, GOS-100, GOS-100-640, GOS-150, GOS-150-640, GOS-220,

**Product Code(s)** GOS-220-640, GOS-320, GOS-320-640, GOS-460, GOS-460-640, GOS-680, GOS-680-640

Synonyms No information available

Recommended use of the chemical and restrictions on use
Recommended Use Gear Oil, Lubricant.
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address
The Lubri-Lov Company

150 Enterprise Dr. Wentzville, MO 63385 TEL: (636) 561-5007

Emergency telephone number

Company Phone Number (636) 561-5007 Company Emergency Phone Number (636) 561-5007

Emergency telephone number Chemtrec 1-800-424-9300

# 2. HAZARDS IDENTIFICATION

# Classification

**OSHA Regulatory Status** 

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization Category 1

## Label elements

## **EMERGENCY OVERVIEW**

# WARNING

# Hazard statements

May cause an allergic skin reaction



Appearance Amber colored liquid

Physical state viscous liquid

Odor Mild petroleum odor Mild sulfur odor

#### **Precautionary Statements - Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

#### **Precautionary Statements - Response**

Specific treatment (see supplemental first aid instruction on this label)

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

# Other information

• May be harmful in contact with skin

Unknown Aquatic Toxicty

64.566% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Common Name** Petroleum based lubricating fluid, Synthetic hydrocarbon lubricating fluid.

**Chemical Family** Petroleum hydrocarbon mixture.

Chemical name	CAS-No	Weight %	Trade secret
1-Decene, homopolymer, hydrogenated	68037-01-4	0-70	*
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	0-75	*
Long-chain alkyl amine	Proprietary	0.07-0.15	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

# First aid measures

General advice No hazards which require special first aid measures.

Eye contact Flush eyes for 30 minutes with water. Get medical attention if irritation persists.

**Skin contact** Wash off immediately with soap and plenty of water.

**Inhalation** Move exposed persons to fresh air. Consult medical personal if breathing issues occur.

**Ingestion** Do NOT induce vomiting. Consult a physician.

## Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

# Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

# Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>). Dry chemical. Foam. Water can be used to keep surrounding materials cool.

Small Fires Always use personal safety equipment. Follow appropriate personal safety procedures, and

extinguishing media.

Contact emergency personnel. **Large Fires** 

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

Combustible material.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO 2).

**Explosion data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

Avoid contact with the skin and the eyes. Eye protection or face shield should be used if Personal protection

material is used under conditions that increase the chances of splattering. Wash skin with soap and water if contact occurs. Launder soiled clothing. If spilled, take caution, as

material can cause surfaces to become very slippery.

**Environmental precautions** 

See Section 12 for additional Ecological Information. **Environmental precautions** 

Methods and material for containment and cleaning up

Methods for containment Cover with earth, sand, or other non-combustible material followed with plastic sheets to

minimize spreading or contact with rain.

Excess liquid material can be collected using a scoop or shovel and stored for recycling or Methods for cleaning up

disposal. Prevent material from entering drains or waterways.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Avoid contact with skin, eyes and clothing. Eye protection or face shield should be used if Advice on safe handling

material is used under conditions that increase the chances of splattering. If contact is made, wash skin with soap and water. Launder soiled clothing. Maximum handling temperature is 70 degrees C (158 F). It is recommended to pump or transfer material at

ambient temperature.

# Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Keep containers closed when not in use. **Storage Conditions** 

Follow first aid measures if contact occurs, and spill procedures if spill occurs. For packaged material: Store in a cool dry area. For bulk material: store in cool dry area. Always follow local, state, and federal guidlines for storage of material for amount stored.

Strong oxidizing agents. Incompatible Products

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Control parameters

Exposure guidelines This product does not contain any hazardous materials with occupational exposure limits

established by the region specific regulatory bodies.

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/face Protection** If splashes are likely to occur, wear:. Goggles. Eye/face Protection.

**Skin and body protection**Long sleeved clothing. Protective gloves can be worn, if material comes in contact with skin

wash with soap and water.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

**General Hygiene Considerations** Remove and wash contaminated clothing before re-use.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Information on basic physical and chemical properties

Physical state viscous liquid

Appearance Amber colored liquid Odor Mild petroleum odor Mild

sulfur odor

ColorAmberOdor thresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available
Melting point/freezing point
Boiling Point/Range No information available
Flash point > 93.3 °C / > 200 °F
Evaporation rate No information available
Flammability (solid, gas)
Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available
No information available

Specific gravity 0.84-0.86

Water solubility
Solubility in other solvents
Partition coefficient
No information available
No information available
No information available

Autoignition temperature

Decomposition temperatureNo information availableKinematic viscosity68-460 @40C mm2/sDynamic viscosityNo information availableExplosive propertiesNo information availableOxidizing propertiesNo information available

Other information

Softening point No information available VOC Content No information available

Synthetic GL-2 EP Industrial Gear Oils: ISO 68, 100, 150, 220, 320, 460, 680

DensityNo information availableBulk densityNo information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

## **Chemical stability**

Stable under normal conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous polymerization** Hazardous polymerization does not occur.

#### Conditions to avoid

Excessive heat. High energy sources of ignition.

#### Incompatible materials

Strong oxidizing agents.

# **Hazardous decomposition products**

None known based on information supplied.

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

Product Information No data available

**Inhalation** Inhalation of vapors in high concentration may cause irritation of respiratory system.

**Eye contact** Avoid contact with eyes. May cause irritation.

**Skin contact** May cause eye/skin irritation. Prolonged skin contact may defat the skin and produce

dermatitis.

**Ingestion** Do NOT taste or swallow.

#### Information on toxicological effects

**Symptoms** No information available.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

Chemical name	ACGIH	IARC	NTP	OSHA
Petroleum distillates,	-	Group 1	-	X
hydrotreated heavy				
paraffinic				
64742-54-7				!

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration hazard
No information available.
No information available.
No information available.

Synthetic GL-2 EP Industrial Gear Oils: ISO 68, 100, 150, 220, 320, 460, 680

## Numerical measures of toxicity - Product Information

**Unknown Aquatic Toxicty** 64.566% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

64.706% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Petroleum distillates, hydrotreated heavy	-	5000: 96 h Oncorhynchus mykiss	1000: 48 h Daphnia magna mg/L
paraffinic		mg/L LC50	EC50
64742-54-7			

# Persistence and degradability

No information available.

#### Bioaccumulation

No information available.

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Method Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

# 14. TRANSPORT INFORMATION

**DOT** Not regulated

<u>IATA</u> PETROLEUM LUBRICATING OIL; NOT REGULATED AS DANGEROUS GOODS FOR

TRANSPORT UNDER ICAO TI OR IATA DGR

# 15. REGULATORY INFORMATION

**International Inventories** 

TSCA Does not comply
DSL/NDSL Does not comply
EINECS/ELINCS Does not comply
ENCS Does not comply
IECSC Does not comply
KECL Does not comply
PICCS Does not comply

# AICS Does not comply

# Legend:

All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

# SARA 311/312 Hazard Categories

Acute health hazard No
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

#### **Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

# U.S. State Regulations

## **California Proposition 65**

This product does not contain any Proposition 65 chemicals

# U.S. State Right-to-Know Regulations

# U.S. EPA Label Information

EPA Pesticide registration number Not Applicable

# **16. OTHER INFORMATION**

NFPA Health hazards 0 Flammability 1 Instability 0 Physical and Chemical

Hazards -

HMIS Health hazards 0 Flammability 1 Physical hazards 0 Personal protection X

**Issuing Date** 02-Feb-2010 **Revision Date** 26-June-2014

**Revision Note** 

(M)SDS sections updated 2 3 5 7 9 10 11 14 15 16

Synthetic GL-2 EP Industrial Gear Oils: ISO 68, 100, 150, 220, 320, 460, 680

Revision Date 26-June-2014

**Disclaimer** 

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of MSDS**